

## Product data sheet

### Ray-O-lite RS

#### Description

All the installation benefits of a surface mounted road stud combined with the brightness of prismatic reflectors as well as the added advantage of a solid, tough engineering grade polymer body.

#### **Declaration of conformity to EN 1463 – 1 & 2 Performance Rating S1 & R2**

#### Applications

- All specified EN1463 S1 & R2 rated work
- Particularly effective on edge lines
- Situations where traditional 'all acrylic' and hollow plastic road studs have failed
- On modern stone mastic asphalt (SMA) porous surfaces where the large footprint will resist sinkage

#### Advantages

- Large 100mm square foot print to help resist sinkage into the road surface
- High efficiency, abrasion resistant prismatic reflectors with typical values 4 times higher than the required EN requirements
- Tough ABS polymer body shell to absorb impact and resist damage
- Special rough mineral base texture to optimise adhesion
- 100% solid construction with inert shock absorbing filler that withstands the impact of over-running traffic

#### Product range

- Ray-O-Lite colours—White, yellow, green, red & blue. 1 & 2 way available
- Packed in boxes of 50
- Suitable for use with our Lakeside Hotmelt adhesive





Lakeside Films Ltd

T: + 44 845 293 8062

W: [www.lakesidefilms.co.uk](http://www.lakesidefilms.co.uk)

E: [info@lakesidefilms.co.uk](mailto:info@lakesidefilms.co.uk)